

Light Measurement Report

Print date: 28-4-2025
Measurement date and time: 28-4-2025 11:44:56 – Measurement no. VFR-250428-0940-MS
Measurement tracking No. and Link: [VT250428-005918](#)
Operator:



Laboratory and Equipment

Laboratory Owner and Location	Viso Systems, Copenhagen V, Denmark
Goniospectrometer System and Type	LabSpion – Type C, horizontal
Sensor Name, Calibr. Date and Serial No.	LabSensor Model2 – 11-1-2024 – 3130191315
Spectrometer Manufacturer and Model	Ibsen Photonics, Denmark – Freedom VIS (Custom Viso)

Measurement Conditions



Number of C-planes and Resolution	12 planes – 30°
γ (gamma)-Resolution	5°
Test Distance	2,00 m
Input Power, Power and Displ. Factors	5,7 W – PF 0,85 – DPF 0,89
Input RMS Voltage and Current	230 V – 0,029 A
Frequency of Input Power	50 Hz
Warm-up Time and Variation	Lamp stabilized in 15 min 1 sec – 2,0%

Tested Light Source

Product Name	273467-3000K
Item No. and Manufacturer	273467-3000K – Dutchfulfillment
Product Description (line 1)	LED INBOUWSPOT VARDA SLIM-FIT 5W DIM2WARM CHROME

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)	307 lm – 0,13% / 99,87%
Efficiency	54 lm/W
Peak Intensity and Beam Angle	217 cd – 78,3°
Correlated Color Temperature, Target/Measured	CCT = 3000 K / 3019 K
Color Rendering Index	CRI 92,3
Color Rendering TM30-18	R _f 91,6 – R _g 97,5
Color Shift, CIE duv and MacAdam Steps	Duv 0,0017 – SDCM 1,7
Flicker	SVM 0,09 – PstLM 0,17



Light Measurement Report

Print date: 28-4-2025

Measurement date and time: 28-4-2025 11:44:56 – Measurement no. VFR-250428-0940-MS


Measurement tracking No. and Link: [VT250428-005918](#)

Operator:



Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	307 lm
Lumen Up% / Down%	0,13% / 99,87%
Peak Intensity	217 cd
Beam Angle (50%)	78,3°
Beam Angle (90%)	78,3°
Beam Angle (10%)	78,3°

Cut-off Angle

Average 2,5%	124,2°
--------------	--------

Field Angle

Average 10%	106,1°
-------------	--------


Intensity Ratio

In 120° cone	97,3%
In 90° cone	85,2%

C000-C180

C090-C270

Linear distribution diagram - Intensity (candela) vs γ-angle



Light Measurement Report

Print date: 28-4-2025


Measurement date and time: 28-4-2025 11:44:56 – Measurement no. VFR-250428-0940-MS

Measurement tracking No. and Link: [VT250428-005918](#)


Operator:



Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)



Light Measurement Report

Print date: 28-4-2025

Measurement date and time: 28-4-2025 11:44:56 – Measurement no. VFR-250428-0940-MS

Measurement tracking No. and Link: [VT250428-005918](#)

Operator:




Color details


Correlated Color Temperature, Target CCT = 3000 K
Correlated Color Temperature, Measured CCT = 3019 K
Color Rendering Index CRI 92,3
Color Rendering Index, R9 (red component) R9 = 51,4
Color Rendering TM30-18 R_f 91,6 – R_g 97,5
Color Quality Scale CQS = 91,0

MacAdam Steps
Color coordinates CIE 1931 (x;y) = (0,437;0,404)
Color coordinate CIEs 1960 (u;v) = (0,251;0,348)
Color deviation from BBL Duv = 0,0017
Color coordinate CIEs 1976 (CIELUV) (u';v') = (0,251;0,521)


CIE 1931



CIE 1931 – zoomed on Planckian locus




Color Rendering Index per reference color (CIE 1995)




CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
92,1	96,0	99,2	92,9	92,0	95,9	91,2	78,8	51,4	90,4	94,7	80,8	93,3	99,2	86,2

Spectral power distribution (SPD) / W/nm – 0-100%




TM30-18 R_f -values per hue bin



TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
89,3	91,8	91,7	95,4	94,1	97,1	93,3	96,9	93,1	89,6	89,4	90,4	91,2	86,9	87,7	85,3

Color Quality Scale by reference color



CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
86,7	95,3	90,8	89,9	92,0	92,9	93,3	94,3	97,1	95,3	94,4	93,6	92,5	84,6	85,5

Light Measurement Report

Print date: 28-4-2025


Measurement date and time: 28-4-2025 11:44:56 – Measurement no. VFR-250428-0940-MS

Measurement tracking No. and Link: [VT250428-005918](#)

Operator:



Beam Details



Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3,3	6,6	9,8	13,1	16,4	19,7	23	26,2	29,5	32,8	36,1	39,4	42,7	45,9	49,2	52,5	55,8	59,1	62,3	65,6	ft
217	54	24	14	9	6	4	3	3	2	2	2	1	1	1	1	1	1	1	1	lux
20,1	5	2,2	1,3	0,8	0,6	0,4	0,3	0,2	0,2	0,2	0,1	0,1	0,1	0,1	0,1	0,1	0,1	0,1	0,1	fc

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
217	215	208	197	182	164	145	125	105	75	37	13	6	4	3	2	2	1	0	0	cd
100%	99%	96%	91%	84%	76%	67%	58%	48%	35%	17%	6%	3%	2%	1%	1%	1%	0%	0%	0%	of 0°val

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
217	215	208	197	182	164	145	125	105	75	37	13	6	4	3	2	2	1	0	0	cd
100%	99%	96%	91%	84%	76%	67%	58%	48%	35%	17%	6%	3%	2%	1%	1%	1%	0%	0%	0%	of 0°val

Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
217	215	208	197	182	164	145	125	105	75	37	13	6	4	3	2	2	1	0	0	cd
100%	99%	96%	91%	84%	76%	67%	58%	48%	35%	17%	6%	3%	2%	1%	1%	1%	0%	0%	0%	of 0°val

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
217	215	208	197	182	164	145	125	105	75	37	13	6	4	3	2	2	1	0	0	cd
100%	99%	96%	91%	84%	76%	67%	58%	48%	35%	17%	6%	3%	2%	1%	1%	1%	0%	0%	0%	of 0°val

Light Measurement Report

Print date: 28-4-2025

Measurement date and time: 28-4-2025 11:44:56 – Measurement no. VFR-250428-0940-MS

Measurement tracking No. and Link: [VT250428-005918](#)

Operator:



Light Planning – UGR table

Uncorrected, comprehensive UGR table according to 117-1995

Reflectances											
	ρ Ceiling	70	70	50	50	30	70	70	50	50	30
	ρ Walls	50	30	50	30	30	50	30	50	30	30
	ρ Floor	20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	23,8	24,6	23,9	24,9	25,1	23,8	24,6	23,9	24,9	25,1
	3H	23,6	24,5	23,9	24,7	24,9	23,6	24,5	23,9	24,7	24,9
	4H	23,5	24,4	23,9	24,6	24,9	23,5	24,4	23,9	24,6	24,9
	6H	23,6	24,3	23,9	24,6	24,9	23,6	24,3	23,9	24,6	24,9
	8H	23,5	24,2	23,8	24,6	25,0	23,5	24,2	23,8	24,6	25,0
	12H	23,5	24,2	23,8	24,5	25,0	23,5	24,2	23,8	24,5	25,0
4H	2H	23,5	24,4	23,9	24,6	24,9	23,5	24,4	23,9	24,6	24,9
	3H	23,5	24,2	23,8	24,5	24,9	23,5	24,2	23,8	24,5	24,9
	4H	23,4	24,0	23,8	24,4	25,0	23,4	24,0	23,8	24,4	25,0
	6H	23,4	24,0	23,9	24,4	24,7	23,4	24,0	23,9	24,4	24,7
	8H	23,3	23,9	23,9	24,3	24,7	23,3	23,9	23,9	24,3	24,7
	12H	23,3	23,8	23,8	24,2	24,7	23,3	23,8	23,8	24,2	24,7
8H	4H	23,3	23,9	23,8	24,2	24,6	23,3	23,9	23,8	24,2	24,6
	6H	23,3	23,7	23,8	24,2	24,7	23,3	23,7	23,8	24,2	24,7
	8H	23,4	23,7	23,9	24,2	24,8	23,4	23,7	23,9	24,2	24,8
	12H	23,3	23,6	23,9	24,1	24,7	23,3	23,6	23,9	24,1	24,7
12H	4H	23,2	23,7	23,7	24,1	24,6	23,2	23,7	23,7	24,1	24,6
	6H	23,3	23,7	23,8	24,2	24,8	23,3	23,7	23,8	24,2	24,8
	8H	23,3	23,6	23,9	24,1	24,7	23,3	23,6	23,9	24,1	24,7
Variations with the observer position for the luminaire spacings, S:											
S = 1.0H		1,7 / -4,9					1,7 / -4,9				
S = 1.5H		3,9 / -6,7					3,9 / -6,7				
S = 2.0H		5,7 / -7,3					5,7 / -7,3				

Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR		(RCR: Room Cavity Ratio)			Room Values are expressed as percentage of Lumen delivered to the task surface													
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91
2	105	100	95	91	103	98	93	90	94	91	88	91	88	86	88	86	84	82
3	99	91	85	80	97	90	84	80	87	82	78	84	80	77	82	79	76	74
4	92	83	77	72	90	82	76	71	80	75	70	78	73	70	76	72	69	67
5	87	77	70	65	85	76	69	64	74	68	64	72	67	63	70	66	62	61
6	81	71	64	58	80	70	63	58	68	62	58	67	61	57	65	61	57	55
7	76	65	58	53	75	65	58	53	63	57	53	62	56	52	61	56	52	50
8	72	61	54	49	70	60	53	49	59	53	48	58	52	48	57	52	48	46
9	68	56	49	45	66	56	49	45	55	49	45	54	48	44	53	48	44	43
10	64	53	46	41	63	52	46	41	51	45	41	50	45	41	50	44	41	39

Light Measurement Report


Print date: 28-4-2025
Measurement date and time: 28-4-2025 11:44:56 – Measurement no. VFR-250428-0940-MS
Measurement tracking No. and Link: [VT250428-005918](#)
Operator:



Luminaire budgetary diagram

Uncorrected, comprehensive UGR table according to 117-1995

LAMPS (number of lamps)



Conditions

H = Room height	Flux = 307 lm	p(%)		
H _{down} = Lamp distance from ceiling =	0.00 m	Line type	Ceiling reflectance	Wall reflectance
H _{work} = Work area height from floor =	0.00 m	-----	70	50
E _{work} = Average lux on work area =	100 lx	-----	50	30
				Floor reflectance
				20

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
20,3 lm	55,1 lm	75,2 lm	78,0 lm	55,9 lm	14,7 lm	4,44 lm	2,45 lm	1,05 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0,063 lm	0,040 lm	0,045 lm	0,043 lm	0,058 lm	0,057 lm	0,044 lm	0,031 lm	0,011 lm

Light Measurement Report

Print date: 28-4-2025

Measurement date and time: 28-4-2025 11:44:56 – Measurement no. VFR-250428-0940-MS

Measurement tracking No. and Link: [VT250428-005918](#)

Operator:



Outdoor Light Planning

Lumen per Zone

Zone (γ)	Lumen	% Total
0-10°	20 lm	6,6%
10-20°	55 lm	17,9%
20-30°	75 lm	24,5%
30-40°	78 lm	25,4%
40-50°	56 lm	18,2%
50-60°	15 lm	4,8%
60-70°	4 lm	1,4%
70-80°	2 lm	0,8%
80-90°	1 lm	0,3%
90-100°	0 lm	0,0%
100-110°	0 lm	0,0%
110-120°	0 lm	0,0%
120-130°	0 lm	0,0%
130-140°	0 lm	0,0%
140-150°	0 lm	0,0%
150-160°	0 lm	0,0%
160-170°	0 lm	0,0%
170-180°	0 lm	0,0%
Total	307 lm	100,0%

Intensity peaks

Max intensity	217 cd
Intensity, 90°	0 cd
Intensity, 0°	217 cd

Zonal Lumen summary

Zone (γ)	Lumen	% Total
0-30°	151 lm	49,0%
0-40°	229 lm	74,3%
0-60°	299 lm	97,3%
60-90°	8 lm	2,6%
70-100°	4 lm	1,2%
90-120°	0 lm	0,0%
0-90°	307 lm	99,9%
90-180°	0 lm	0,1%
0-180°	307 lm	100,0%


BUG rating

	Lumen	% Total
Forward light		
Low(0-30°)	75 lm	24,5%
Medium(30-60°)	74 lm	24,2%
High(60-80°)	3 lm	1,1%
Very high(80-90°)	1 lm	0,2%
Back light		
Low(0-30°)	75 lm	24,5%
Medium(30-60°)	74 lm	24,2%
High(60-80°)	3 lm	1,1%
Very high(80-90°)	1 lm	0,2%
Uplight		
Low(90-100°)	0 lm	0,0%
High(100-180°)	0 lm	0,1%

IESNA TM-15-07

Luminaire Classification System For Outdoor Luminaires

BUG rating B0 U0 G0



Light Measurement Report

Print date: 28-4-2025
Measurement date and time: 28-4-2025 11:44:56 – Measurement no. VFR-250428-0940-MS
Measurement tracking No. and Link: [VT250428-005918](#)
Operator:




Power Details

Input Power

Power feed to light source	5,7 W
Frequency of input power	50 Hz
RMS Input voltage feed, V_{RMS}	230 V
RMS Input current feed, I_{RMS}	0,029 A
Volt-Ampere or apparent power = $V_{RMS} \cdot I_{RMS}$	6,66 VA
Displacement factor of AC power feed	0,89
Power factor of AC current feed	0,85
Total harmonic distortion of the current	29,57%
Total harmonic distortion of the voltage	0,14%

Input Power Curve



Efficiency

Radiated power efficiency	18,1%
Lumen efficiency	54 lm/W

Stabilization Details

Warmup Conditions

Stable period	15 min
Stable change max	2,0%
Minimum time	15 min

Color Temperature Change

CCT start	2993 K
CCT shift	+7 K
CCT end	3000 K


Warmup Result

Total warmup time	Lamp stabilized in 15 min 1 sec
Warmup variation	-0,3%

Output Change

Output start	308 lm
Output change	-1 lm
Output end	307 lm

Stabilization Curve



Light Measurement Report

Print date: 28-4-2025
Measurement date and time: 28-4-2025 11:44:56 – Measurement no. VFR-250428-0940-MS
Measurement tracking No. and Link: [VT250428-005918](#)
Operator:



Flicker /TLA details

Flicker Meter Type Viso Systems LabFlicker
Frequency of input power 50 Hz
Flicker/TLA sample rate 20000 samples/s

Measurement time
PstLM 180 sec
All other indices 1,2 sec


Flicker indices according to Illuminating Engineering Society (IES)
Flicker frequency 99,5 Hz
Percent Flicker 4,29 %
Flicker index 0,01

Flicker indices according to California Energy Commission (CEC) 2016b
JA8/10 40 Hz 0,19 %
JA8/10 90 Hz 0,23 %
JA8/10 200 Hz 2,79 %
JA8/10 400 Hz 3,63 %
JA8/10 1000 Hz 4,27 %


TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)
PstLM value (F < 80 Hz) 0,17
SVM value (80 < F < 2000 Hz) 0,09

Flicker indices according to Lighting Research Center (2015)
Perception metric, Assist Mp 0,1

Flicker frame (frame of one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789 Frequency/modulation plot

