

Light efficiency:

-2012233 Lumen/Watt

Light quality:

CRI: 70,0

Color temperature:

5500 K

Output: 156 lm

Peak: 59,0 cd

Power: 0,00 W

PF: -0,01



Tracking number: [VT240909-002829](#)

Product name:

800673

Item number:


800673

Date and time:

9-9-2024 13:34:44

Description:

NOODVERLICHTING | INBOUWSPOT |



Beam angle

153,6°




CIE 1931


x: 0,333


y: 0,341

Spectra




Power







TM-30: 70,7



CRI: 70,0 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
68,4	73,4	76,1	71,9	69,1	64,0	78,4	58,4	-30,8	36,3	69,7	39,4	68,4	86,4	62,0


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
67,1	74,1	59,5	65,0	73,2	81,7	83,8	75,6	78,2	60,4	53,5	69,9	80,0	75,3	70,9	75,8

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
77,6	91,5	59,3	56,0	67,3	70,2	73,9	84,6	88,3	69,6	64,7	66,6	69,7	56,9	65,4

CQS: 69,0



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
5500 K	70,0	-30,8	70,7	95,3	69,0	0,333	0,341	0,207	0,318	0,0002







Rf 70,7


Fidelity index Rf

Rg 95,3

Gamut index Rg

Hue Bin	R _f	Shifts (%)	
		Chroma	Hue
1	67	-17%	-5%
2	74	-13%	9%
3	60	-7%	23%
4	65	5%	22%
5	73	13%	14%
6	82	12%	-1%
7	84	2%	-11%
8	76	-10%	-11%
9	78	-19%	2%
10	60	-15%	19%
11	54	-5%	29%
12	70	5%	20%
13	80	15%	7%
14	75	12%	-6%
15	71	8%	-24%
16	76	-5%	-14%




Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
13lx	3lx	1lx	1lx	1lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx
1,2fcd	0,3fcd	0,1fcd	0,1fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
13,4	13,2	12,9	12,8	13,1	13,7	14,7	16,1	17,9	20,3	23,3	27,4	34,6	46,6	57,0	43,4	13,4	2,2	0,6	0,2
100%	99%	96%	95%	98%	102%	110%	120%	134%	152%	174%	205%	258%	348%	426%	324%	100%	17%	5%	1%

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
13,4	13,2	12,9	12,8	13,1	13,7	14,7	16,1	17,9	20,3	23,3	27,4	34,6	46,6	57,0	43,4	13,4	2,2	0,6	0,2
100%	99%	96%	95%	98%	102%	110%	120%	134%	152%	174%	205%	258%	348%	426%	324%	100%	17%	5%	1%


Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
13,4	13,2	12,9	12,8	13,1	13,7	14,7	16,1	17,9	20,3	23,3	27,4	34,6	46,6	57,0	43,4	13,4	2,2	0,6	0,2
100%	99%	96%	95%	98%	102%	110%	120%	134%	152%	174%	205%	258%	348%	426%	324%	100%	17%	5%	1%

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
13,4	13,2	12,9	12,8	13,1	13,7	14,7	16,1	17,9	20,3	23,3	27,4	34,6	46,6	57,0	43,4	13,4	2,2	0,6	0,2
100%	99%	96%	95%	98%	102%	110%	120%	134%	152%	174%	205%	258%	348%	426%	324%	100%	17%	5%	1%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
153,6°	164,4°	173,3°	39,8%	18,2%


iso-candela diagram


10%	1 cd
20%	3 cd
30%	4 cd
40%	5 cd
50%	7 cd
60%	8 cd
70%	9 cd
80%	11 cd
90%	12 cd

Conditions:

Number of c-planes: 72

Candela at center: 13 cd

iso-lux diagram


3%	4,02m lx
5%	6,70m lx
10%	13,4m lx
30%	40,2m lx
50%	67,0m lx

Conditions:

Number of c-planes: 72

Lux at center: 0,134 lx

*Lux distribution on a surface
when lamp is mounted at 10
meters from the surface.*

Glare evaluation according to UGR


p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	27,9	29,6	28,3	30,1	30,3	27,9	29,6	28,3	30,1	30,3
	3H	32,6	34,3	33,0	34,7	34,9	32,6	34,3	33,0	34,7	34,9
	4H	34,0	35,7	34,4	36,0	36,3	34,0	35,7	34,4	36,0	36,3
	6H	34,4	36,0	34,7	36,2	36,6	34,4	36,0	34,7	36,2	36,6
	8H	34,4	35,9	34,8	36,2	36,6	34,4	35,9	34,8	36,2	36,6
	12H	34,4	35,8	34,7	36,1	36,6	34,4	35,8	34,7	36,1	36,6
4H	2H	29,7	31,4	30,1	31,7	32,0	29,7	31,4	30,1	31,7	32,0
	3H	34,1	35,5	34,5	35,9	36,4	34,1	35,5	34,5	35,9	36,4
	4H	35,4	36,7	35,8	37,1	37,7	35,4	36,7	35,8	37,1	37,7
	6H	35,8	37,0	36,3	37,4	37,8	35,8	37,0	36,3	37,4	37,8
	8H	35,8	36,9	36,3	37,3	37,7	35,8	36,9	36,3	37,3	37,7
	12H	35,8	36,7	36,3	37,2	37,7	35,8	36,7	36,3	37,2	37,7
8H	4H	35,8	36,9	36,3	37,3	37,7	35,8	36,9	36,3	37,3	37,7
	6H	36,2	37,2	36,7	37,6	38,2	36,2	37,2	36,7	37,6	38,2
	8H	36,3	37,1	36,8	37,6	38,3	36,3	37,1	36,8	37,6	38,3
	12H	36,3	37,0	36,9	37,5	38,1	36,3	37,0	36,9	37,5	38,1
12H	4H	35,8	36,8	36,3	37,2	37,7	35,8	36,8	36,3	37,2	37,7
	6H	36,2	37,1	36,8	37,6	38,3	36,2	37,1	36,8	37,6	38,3
	8H	36,3	37,0	36,9	37,5	38,2	36,3	37,0	36,9	37,5	38,2
Variation of the observer position for the luminaire distance S											
S = 1.0H		0,1 / -0,1					0,1 / -0,1				
S = 1.5H		0,2 / -0,2					0,2 / -0,2				
S = 2.0H		0,4 / -0,4					0,4 / -0,4				
CIE 117-1995. Corrected glare indices referring to 156 lm total luminous flux											

Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	103	96	89	83	100	93	87	82	89	84	79	84	80	77	81	77	74	72
2	88	76	66	58	85	74	65	57	70	62	55	66	60	54	63	57	52	50
3	77	62	51	41	74	60	50	41	57	48	40	54	46	39	51	44	38	35
4	68	52	40	31	66	51	40	31	48	38	30	45	37	30	43	35	29	26
5	62	45	33	24	59	44	32	24	41	31	24	39	30	23	37	29	23	20
6	56	39	28	20	54	38	27	20	36	26	19	34	25	19	32	25	19	16
7	51	35	24	16	49	34	24	16	32	23	16	30	22	16	29	21	16	13
8	48	31	21	14	46	30	21	14	29	20	14	27	19	13	26	19	13	11
9	44	28	19	12	43	28	18	12	26	18	12	25	17	12	24	17	11	9
10	41	26	17	11	40	25	16	10	24	16	10	23	16	10	22	15	10	8

LAMPS (number of lamps)

Luminaire budgetary diagram




Zonal Lumen Summary


0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
{LUM0-10}	3,63 lm	6,38 lm	10,1 lm	15,8 lm	24,8 lm	46,7 lm	43,5 lm	3,22 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0,199 lm	0,045 lm	0,041 lm	0,039 lm	0,028 lm	0,020 lm	0,015 lm	0,011 lm	0,003 lm

LCS table

BUG rating:	B0 U0 G0	
Forward light	Lumens	Lumens %
Low(0-30):	5,6	3,6%
Medium(30-60):	25,5	16,4%
High(60-80):	44,5	28,6%
Very high(80-90):	2	1,3%
Back light		
Low(0-30):	5,6	3,6%
Medium(30-60):	25,5	16,4%
High(60-80):	44,5	28,6%
Very high(80-90):	2	1,3%
Uplight		
Low(90-100):	0,2	0,1%
High(100-180):	0,2	0,1%

LCS graph



Warmup curve

Warmup result

Warmup time:	Lamp stabilized in 15 min 1 sec
Warmup variation	-0,3%

Warmup conditions

Stable period:	15 min
Stable change max:	2,0%
Minimum time:	15 min



Color temperature change

CCT start	CCT change	CCT end
5492 K	+8 K	5500 K

Output change

Output start	Output change	Output end
156 lm	lm	156 lm

Flicker curve (complete sampled flicker signal)

Flicker frame (frame of one flicker period)

Flicker FFT (frequency scope of flicker curve)

Flicker results:

Flicker frequency:		12,23 Hz	
Flicker index:	0	JA8/10 40Hz	0,03 %
Flicker percentage:	0,08 %	JA8/10 90Hz	0,04 %
SVM: (Visual flicker)	0	JA8/10 200Hz	0,05 %
PstLM	0,05	JA8/10 400Hz	0,06 %
Mp	0,02	JA8/10 1000Hz	0,07 %

Flicker conditions:

Sample rate:	20000 samples/second
--------------	----------------------