

Light Measurement Report

Print date: 26-11-2024

Measurement date and time: 26-11-2024 09:09:29 – Measurement no. VFR-241126-2152-MS

Measurement tracking No. and Link: [n/a](#)

Operator:



Laboratory and Equipment

Laboratory Owner and Location
Goniospectrometer System and Type
Sensor Name, Calibr. Date and Serial No.
Spectrometer Manufacturer and Model

Viso Systems, Copenhagen V, Denmark
LabSpion – Type C, horizontal
LabSensor Model2 – 11-1-2024 – 3130191315
Ibsen Photonics, Denmark – Freedom VIS (Custom Viso)

Measurement Conditions

Number of C-planes and Resolution
 γ (gamma)-Resolution
Test Distance
Input Power, Power and Displ. Factors
Input RMS Voltage and Current
Frequency of Input Power
Warm-up Time and Variation

12 planes – 30°
5°
1,99 m
10,7 W – PF 0,78 – DPF 0,95
230 V – 0,060 A
50 Hz
Lamp stabilized in 16 min 40 sec – 2,0%

Tested Light Source



Product Name
Item No. and Manufacturer
Product Description (line 1)
SWITCH

807887-3000K-10W
807887-3000K-10W – Dutchfulfillment
3-FASE RAILSPOT | ROSALIN | 10W-20W-30W | WIT | DIMBAAR | CCT-

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)
Efficiency
Peak Intensity and Beam Angle
Correlated Color Temperature, Target/Measured
Color Rendering Index
Color Rendering TM30-18
Color Shift, CIE duv and MacAdam Steps
Flicker

878 lm – 0,09% / 99,91%
82 lm/W
1991 cd – 32,6°
CCT = 3000 K / 3446 K
CRI 93,3
 R_f 91,1 – R_g 97,6
Duv 0,0019 – SDCM 13,8
SVM 0,09 – PstLM 0,05



Light Measurement Report

Print date: 26-11-2024

Measurement date and time: 26-11-2024 09:09:29 – Measurement no. VFR-241126-2152-MS


Measurement tracking No. and Link: [n/a](#)

Operator:



Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	878 lm
Lumen Up% / Down%	0,09% / 99,91%
Peak Intensity	1991 cd
Beam Angle (50%)	32,6°
Beam Angle (90%)	32,6°
Beam Angle (10%)	32,6°

Cut-off Angle

Average 2,5%	86,9°
--------------	-------

Field Angle

Average 10%	73,5°
-------------	-------


Intensity Ratio

In 120° cone	99,5%
In 90° cone	97,9%

C000-C180

C090-C270

Linear distribution diagram - Intensity (candela) vs γ -angle



Light Measurement Report

Print date: 26-11-2024


Measurement date and time: 26-11-2024 09:09:29 – Measurement no. VFR-241126-2152-MS

Measurement tracking No. and Link: [n/a](#)

Operator:




Iso-intensity Diagram (Iso-candela)



90 %	1792,2 cd
80 %	1593,1 cd
70 %	1393,9 cd
60 %	1194,8 cd
50 %	995,7 cd
40 %	796,5 cd
30 %	597,4 cd
20 %	398,3 cd
10 %	199,1 cd

Peak intensity: 1991,4 cd
Number of c-planes: 12

Iso-illuminance Diagram (Iso-lux)



50,0 %	110,6 lx
30,0 %	66,4 lx
10,0 %	22,1 lx
5,0 %	11,1 lx
3,0 %	6,6 lx

Peak illuminance: 221,3 lx
Mounting height: 3,0 m
Number of c-planes: 12

Light Measurement Report

Print date: 26-11-2024

Measurement date and time: 26-11-2024 09:09:29 – Measurement no. VFR-241126-2152-MS

Measurement tracking No. and Link: [n/a](#)

Operator:



Color details

Correlated Color Temperature, Target CCT = 3000 K
 Correlated Color Temperature, Measured CCT = 3446 K
 Color Rendering Index CRI 93,3
 Color Rendering Index, R9 (red component) R9 = 59,8
 Color Rendering TM30-18 R_f 91,1 – R_g 97,6
 Color Quality Scale CQS = 92,6

MacAdam Steps SDCM = 13,8
 Color coordinates CIE 1931 (x;y) = (0,437;0,404)
 Color coordinate CIEs 1960 (u;v) = (0,251;0,348)
 Color deviation from BBL Duv = 0,0019
 Color coordinate CIEs 1976 (CIELUV) (u';v') = (0,251;0,521)


CIE 1931



CIE 1931 – zoomed on Planckian locus




Color Rendering Index per reference color (CIE 1995)




CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
93,6	96,4	98,3	93,9	92,9	95,0	93,3	83,4	59,8	90,7	95,3	74,9	94,5	98,5	88,9

Spectral power distribution (SPD) / W/nm – 0-100%




TM30-18 R_f-values per hue bin



TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
90,0	93,1	92,9	94,0	92,9	97,1	93,2	95,1	91,6	87,3	87,1	89,9	92,5	87,7	87,8	86,7

Color Quality Scale by reference color



CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
89,1	97,1	90,1	89,2	92,4	94,0	95,1	95,9	99,0	96,7	96,2	95,8	95,1	88,3	88,9

Light Measurement Report

Print date: 26-11-2024


Measurement date and time: 26-11-2024 09:09:29 – Measurement no. VFR-241126-2152-MS

Measurement tracking No. and Link: [n/a](#)

Operator:



Beam Details



Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3,3	6,6	9,8	13,1	16,4	19,7	23	26,2	29,5	32,8	36,1	39,4	42,7	45,9	49,2	52,5	55,8	59,1	62,3	65,6	ft
1991	498	221	124	80	55	41	31	25	20	16	14	12	10	9	8	7	6	6	5	lux
185	46,3	20,6	11,6	7,4	5,1	3,8	2,9	2,3	1,9	1,5	1,3	1,1	0,9	0,8	0,7	0,6	0,6	0,5	0,5	fc

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
1991	1972	1882	1792	1656	1501	1344	1181	1019	873	735	608	524	439	389	352	313	265	218	165	cd
100%	99%	95%	90%	83%	75%	67%	59%	51%	44%	37%	31%	26%	22%	20%	18%	16%	13%	11%	8%	of 0°val

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
1991	1972	1882	1792	1656	1501	1344	1181	1019	873	735	608	524	439	389	352	313	265	218	165	cd
100%	99%	95%	90%	83%	75%	67%	59%	51%	44%	37%	31%	26%	22%	20%	18%	16%	13%	11%	8%	of 0°val

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
1991	1972	1882	1792	1656	1501	1344	1181	1019	873	735	608	524	439	389	352	313	265	218	165	cd
100%	99%	95%	90%	83%	75%	67%	59%	51%	44%	37%	31%	26%	22%	20%	18%	16%	13%	11%	8%	of 0°val

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
1991	1972	1882	1792	1656	1501	1344	1181	1019	873	735	608	524	439	389	352	313	265	218	165	cd
100%	99%	95%	90%	83%	75%	67%	59%	51%	44%	37%	31%	26%	22%	20%	18%	16%	13%	11%	8%	of 0°val

Light Measurement Report

Print date: 26-11-2024

Measurement date and time: 26-11-2024 09:09:29 – Measurement no. VFR-241126-2152-MS

Measurement tracking No. and Link: [n/a](#)

Operator:



Light Planning – UGR table

Uncorrected, comprehensive UGR table according to 117-1995

Reflectances		70	70	50	50	30	70	70	50	50	30
	ρ Ceiling	70	70	50	50	30	70	70	50	50	30
	ρ Walls	50	30	50	30	30	50	30	50	30	30
	ρ Floor	20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	16,4	16,9	16,5	17,2	17,3	16,4	16,9	16,5	17,2	17,3
	3H	16,1	16,8	16,4	17,0	17,2	16,1	16,8	16,4	17,0	17,2
	4H	16,0	16,7	16,4	16,9	17,1	16,0	16,7	16,4	16,9	17,1
	6H	16,0	16,6	16,3	16,9	17,2	16,0	16,6	16,3	16,9	17,2
	8H	15,9	16,5	16,3	16,8	17,2	15,9	16,5	16,3	16,8	17,2
	12H	15,9	16,4	16,2	16,8	17,2	15,9	16,4	16,2	16,8	17,2
4H	2H	16,0	16,7	16,4	16,9	17,1	16,0	16,7	16,4	16,9	17,1
	3H	15,9	16,4	16,3	16,8	17,2	15,9	16,4	16,3	16,8	17,2
	4H	15,8	16,2	16,2	16,7	17,2	15,8	16,2	16,2	16,7	17,2
	6H	15,7	16,2	16,2	16,5	16,9	15,7	16,2	16,2	16,5	16,9
	8H	15,6	16,1	16,1	16,4	16,8	15,6	16,1	16,1	16,4	16,8
	12H	15,6	15,9	16,1	16,3	16,8	15,6	15,9	16,1	16,3	16,8
8H	4H	15,6	16,1	16,1	16,4	16,8	15,6	16,1	16,1	16,4	16,8
	6H	15,6	15,9	16,1	16,3	16,9	15,6	15,9	16,1	16,3	16,9
	8H	15,6	15,8	16,1	16,3	16,9	15,6	15,8	16,1	16,3	16,9
	12H	15,5	15,7	16,1	16,2	16,8	15,5	15,7	16,1	16,2	16,8
12H	4H	15,6	15,9	16,1	16,3	16,8	15,6	15,9	16,1	16,3	16,8
	6H	15,6	15,8	16,1	16,3	16,9	15,6	15,8	16,1	16,3	16,9
	8H	15,5	15,7	16,1	16,2	16,8	15,5	15,7	16,1	16,2	16,8

Variations with the observer position for the luminaire spacings, S:

S = 1.0H	5,0 / -12,4	5,0 / -12,4
S = 1.5H	7,6 / -15,2	7,6 / -15,2
S = 2.0H	9,6 / -17,7	9,6 / -17,7

Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)																	
	Room Values are expressed as percentage of Lumen delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	109	107	112	109	107	105	105	104	102	102	100	99	98	97	96	95
2	109	105	101	98	107	103	100	97	100	97	95	97	95	93	94	92	91	89
3	104	98	94	90	102	97	93	90	95	91	88	92	89	87	90	88	86	84
4	100	93	88	84	98	92	87	84	90	86	83	88	84	82	86	83	81	79
5	95	88	83	79	94	87	82	79	85	81	78	84	80	77	82	79	77	75
6	91	83	78	74	90	83	78	74	81	77	74	80	76	73	79	75	73	71
7	88	79	74	70	86	79	74	70	77	73	70	76	72	69	75	72	69	68
8	84	76	70	67	83	75	70	66	74	69	66	73	69	66	72	68	66	64
9	81	72	67	63	80	72	67	63	71	66	63	70	66	63	69	65	63	61
10	78	69	64	60	77	69	64	60	68	63	60	67	63	60	66	63	60	59

Light Measurement Report

Print date: 26-11-2024

Measurement date and time: 26-11-2024 09:09:29 – Measurement no. VFR-241126-2152-MS

Measurement tracking No. and Link: [n/a](#)


Operator:



Luminaire budgetary diagram

Uncorrected, comprehensive UGR table according to 117-1995

LAMPS (number of lamps)



Conditions

H = Room height	Flux = 878 lm	$\rho(\%)$			
H _{down} = Lamp distance from ceiling =	0.00 m	Line type	Ceiling reflectance	Wall reflectance	Floor reflectance
H _{work} = Work area height from floor =	0.00 m	-----	70	50	30
E _{work} = Average lux on work area =	100 lx	_____	50	30	20

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
166 lm	302 lm	223 lm	148 lm	28,5 lm	7,05 lm	2,60 lm	0,810 lm	0,147 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0,092 lm	0,085 lm	0,087 lm	0,089 lm	0,085 lm	0,103 lm	0,117 lm	0,100 lm	0,033 lm

Light Measurement Report

Print date: 26-11-2024

Measurement date and time: 26-11-2024 09:09:29 – Measurement no. VFR-241126-2152-MS

Measurement tracking No. and Link: [n/a](#)

Operator:



Outdoor Light Planning

Lumen per Zone

Zone (γ)	Lumen	% Total
0-10°	166 lm	18,9%
10-20°	302 lm	34,4%
20-30°	223 lm	25,4%
30-40°	148 lm	16,8%
40-50°	29 lm	3,3%
50-60°	7 lm	0,8%
60-70°	3 lm	0,3%
70-80°	1 lm	0,1%
80-90°	0 lm	0,0%
90-100°	0 lm	0,0%
100-110°	0 lm	0,0%
110-120°	0 lm	0,0%
120-130°	0 lm	0,0%
130-140°	0 lm	0,0%
140-150°	0 lm	0,0%
150-160°	0 lm	0,0%
160-170°	0 lm	0,0%
170-180°	0 lm	0,0%
Total	878 lm	100,0%

Intensity peaks

Max intensity	1991 cd
Intensity, 90°	0 cd
Intensity, 0°	1991 cd

Zonal Lumen summary


Zone (γ)	Lumen	% Total
0-30°	690 lm	78,6%
0-40°	838 lm	95,5%
0-60°	873 lm	99,5%
60-90°	4 lm	0,4%
70-100°	1 lm	0,1%
90-120°	0 lm	0,0%
0-90°	877 lm	99,9%
90-180°	1 lm	0,1%
0-180°	878 lm	100,0%

BUG rating

	Lumen	% Total
Forward light		
Low(0-30°)	345 lm	39,3%
Medium(30-60°)	92 lm	10,5%
High(60-80°)	2 lm	0,2%
Very high(80-90°)	0 lm	0,0%
Back light		
Low(0-30°)	345 lm	39,3%
Medium(30-60°)	92 lm	10,5%
High(60-80°)	2 lm	0,2%
Very high(80-90°)	0 lm	0,0%
Uplight		
Low(90-100°)	0 lm	0,0%
High(100-180°)	1 lm	0,1%

IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B1 U1 G0



Light Measurement Report

Print date: 26-11-2024

Measurement date and time: 26-11-2024 09:09:29 – Measurement no. VFR-241126-2152-MS

Measurement tracking No. and Link: [n/a](#)

Operator:




Power Details


Input Power

Power feed to light source	10,7 W
Frequency of input power	50 Hz
RMS Input voltage feed, V_{RMS}	230 V
RMS Input current feed, I_{RMS}	0,060 A
Volt-Ampere or apparent power = $V_{RMS} * I_{RMS}$	13,77 VA
Displacement factor of AC power feed	0,95
Power factor of AC current feed	0,78
Total harmonic distortion of the current	69,81%
Total harmonic distortion of the voltage	0,06%

Input Power Curve



Efficiency



Stabilization Details

Warmup Conditions

Stable period	15 min
Stable change max	2,0%
Minimum time	15 min

Color Temperature Change

CCT start	3000 K
CCT shift	+0 K
CCT end	3000 K


Warmup Result

Total warmup time	Lamp stabilized in 16 min 40 sec
Warmup variation	+2,3%

Output Change

Output start	858 lm
Output change	+20 lm
Output end	878 lm

Stabilization Curve



Light Measurement Report

Print date: 26-11-2024

Measurement date and time: 26-11-2024 09:09:29 – Measurement no. VFR-241126-2152-MS

Measurement tracking No. and Link: [n/a](#)

Operator:



Flicker /TLA details

Flicker Meter Type: Viso Systems LabFlicker
 Frequency of input power: 50 Hz
 Flicker/TLA sample rate: 20000 samples/s

Measurement time
 PstLM: 180 sec
 All other indices: 1,2 sec

Flicker indices according to Illuminating Engineering Society (IES)

Flicker frequency: 99,5 Hz
 Percent Flicker: 2,6 %
 Flicker index: 0,01

Flicker indices according to California Energy Commission (CEC) 2016b

JA8/10 40 Hz: 0,07 %
 JA8/10 90 Hz: 0,08 %
 JA8/10 200 Hz: 2,33 %
 JA8/10 400 Hz: 2,5 %
 JA8/10 1000 Hz: 2,58 %


TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)

PstLM value (F < 80 Hz): 0,05
 SVM value (80 < F < 2000 Hz): 0,09


Flicker indices according to Lighting Research Center (2015)

Perception metric, Assist Mp: 0,04

Flicker frame (frame of one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789 Frequency/modulation plot

