

Data sheet

Commercial Art.No.: 92.030.3153.1

distributor GST18I3VK2P1TBV SW

gesis® CLASSIC T-distributor, with fastening option to 07.413.6853.1/0, cascable,
number of poles 3, rated voltage 250 V, rated current 20 A, number of inputs 1,
number of outputs 2, color of coding/ contact carrier black



certificates / approvals



Technical data

general

rated current	20 A
rated voltage	250 V
rated impulse voltage	4 kV
pollution degree	2
mechanical coding	code 1
lockable	self-locking (unlocking by tool)
color of coding/ contact carrier	black
marking of poles	L, N, PE
RAL-number coding/insert connector	9005

model

number of inputs	1
number of outputs	2
type of fastening	yes
degree of protection (IP)	IP40
type of distributor	T-distributor

material

housing material	polyamide
halogen free	yes
contact material	CuZn
fire load	0.095 kWh/St
insulation components continuous temperature	100 °C
surface finish	tin-plated

dimensions

length	57.3 mm
width	37 mm
height	44.8 mm

classification

ECLASS 11	
ECLASS 8.1	27440603
ETIM 9.0	EC002567
ETIM 8.0	EC002567
ETIM 7.0	EC002567
ETIM 6.0	EC002567
ETIM 5.0	EC002567
ETIM 4.0	EC002567

product compliance

ROHS conformity status	compliant/exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1