

# Light Measurement Report

Print date: 2-9-2025

Measurement date and time: 2-9-2025 09:25:10 – Measurement no. VFR-250902-2869-MS

Measurement tracking No. and Link: [VT250902-002432](#)

Operator:



## Laboratory and Equipment

Laboratory Owner and Location  
Goniospectrometer System and Type  
Sensor Name, Calibr. Date and Serial No.  
Spectrometer Manufacturer and Model

Viso Systems, Copenhagen V, Denmark  
LabSpion – Type C, horizontal  
LabSensor Model2 – 11-1-2024 – 3130191315  
Ibsen Photonics, Denmark – Freedom VIS (Custom Viso)

## Measurement Conditions

Number of C-planes and Resolution  
 $\gamma$  (gamma)-Resolution  
Test Distance  
Input Power, Power and Displ. Factors  
Input RMS Voltage and Current  
Frequency of Input Power  
Warm-up Time and Variation

36 planes – 10°  
5°  
12,09 m  
77,2 W – PF 0,98 – DPF 0,98  
230 V – 0,343 A  
50 Hz  
Lamp stabilized in 15 min 1 sec – 2,0%

## Tested Light Source



Product Name  
Item No. and Manufacturer  
Product Description (line 1)

813741-5700K  
813741-5700K – Dutchfulfillment  
LICHTLIJN MODULE | JUPITER | 65-80W | 60° | 5700K

## Main Light Measurement Results

Output – Total Lumen (Up% / Down%)  
Efficiency  
Peak Intensity and Beam Angle  
Correlated Color Temperature, Target/Measured  
Color Rendering Index  
Color Rendering TM30-18  
Color Shift, CIE duv and MacAdam Steps  
Flicker

12922 lm – 0,99% / 99,01%  
167 lm/W  
7396 cd – 78,2°  
CCT = 5700 K / 5493 K  
CRI 82,5  
 $R_f$  81,8 –  $R_g$  96,8  
Duv 0,0028 – SDCM 4,7  
SVM 0,01 – PstLM 0,01



# Light Measurement Report

Print date: 2-9-2025

Measurement date and time: 2-9-2025 09:25:10 – Measurement no. VFR-250902-2869-MS


Measurement tracking No. and Link: [VT250902-002432](#)

Operator:



## Luminous Intensity diagram

Unit: 0-100% of peak intensity



## Main Values

Output (total Lumen)	12922 lm
Lumen Up% / Down%	0,99% / 99,01%
Peak Intensity	7396 cd
Beam Angle (50%)	78,2°
Beam Angle (90%)	62,5°
Beam Angle (10%)	107,8°

## Cut-off Angle

Average 2,5%	156,6°
--------------	--------

## Field Angle

Average 10%	117,7°
-------------	--------


## Intensity Ratio

In 120° cone	89,5%
In 90° cone	71,7%

**C000-C180**

**C090-C270**

## Linear distribution diagram - Intensity (candela) vs $\gamma$ -angle



# Light Measurement Report

Print date: 2-9-2025


Measurement date and time: 2-9-2025 09:25:10 – Measurement no. VFR-250902-2869-MS

Measurement tracking No. and Link: [VT250902-002432](#)

Operator:




## Iso-intensity Diagram (Iso-candela)



90 %	6650,1 cd
80 %	5911,2 cd
70 %	5172,3 cd
60 %	4433,4 cd
50 %	3694,5 cd
40 %	2955,6 cd
30 %	2216,7 cd
20 %	1477,8 cd
10 %	738,9 cd

Peak intensity: 7389,0 cd  
Number of c-planes: 36

## Iso-illuminance Diagram (Iso-lux)



50,0 %	410,2 lx
30,0 %	246,1 lx
10,0 %	82,0 lx
5,0 %	41,0 lx
3,0 %	24,6 lx

Peak illuminance: 820,4 lx  
Mounting height: 3,0 m  
Number of c-planes: 36

# Light Measurement Report

Print date: 2-9-2025

Measurement date and time: 2-9-2025 09:25:10 – Measurement no. VFR-250902-2869-MS

Measurement tracking No. and Link: [VT250902-002432](#)

Operator:




## Color details


Correlated Color Temperature, Target CCT = 5700 K  
 Correlated Color Temperature, Measured CCT = 5493 K  
 Color Rendering Index CRI 82,5  
 Color Rendering Index, R9 (red component) R9 = 24,8  
 Color Rendering TM30-18 R<sub>f</sub> 81,8 – R<sub>g</sub> 96,8  
 Color Quality Scale CQS = 79,9

MacAdam Steps SDCM = 4,7  
 Color coordinates CIE 1931 (x;y) = (0,328;0,337)  
 Color coordinate CIEs 1960 (u;v) = (0,205;0,317)  
 Color deviation from BBL Duv = 0,0028  
 Color coordinate CIEs 1976 (CIELUV) (u';v') = (0,205;0,475)


### CIE 1931



### CIE 1931 – zoomed on Planckian locus




### Color Rendering Index per reference color (CIE 1995)




CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
82,3	85,3	84,9	83,4	81,1	78,5	89,2	75,5	24,8	62,3	81,1	51,0	82,8	91,2	79,4

### Spectral power distribution (SPD) / W/nm – 0-100%




### TM30-18 R<sub>f</sub>-values per hue bin



TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
78,8	84,7	77,6	82,7	84,8	91,5	91,9	86,0	82,7	69,6	68,1	84,1	86,8	84,7	75,2	86,7

### Color Quality Scale by reference color



CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
86,5	97,0	70,4	66,6	75,8	80,0	83,8	89,8	92,0	81,3	78,5	80,5	83,0	76,1	79,7

# Light Measurement Report

Print date: 2-9-2025


Measurement date and time: 2-9-2025 09:25:10 – Measurement no. VFR-250902-2869-MS

Measurement tracking No. and Link: [VT250902-002432](https://www.viso-systems.com/VT250902-002432)

Operator:



## Beam Details



### Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3,3	6,6	9,8	13,1	16,4	19,7	23	26,2	29,5	32,8	36,1	39,4	42,7	45,9	49,2	52,5	55,8	59,1	62,3	65,6	ft
7379	1845	820	461	295	205	151	115	91	74	61	51	44	38	33	29	26	23	20	18	lux
685,6	171,4	76,2	42,8	27,4	19	14	10,7	8,5	6,9	5,7	4,8	4,1	3,5	3	2,7	2,4	2,1	1,9	1,7	fc

### Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
7379	7368	7317	7231	7111	6953	6745	6488	6158	5700	5048	4158	3120	2128	1329	758	377	145	41	17	cd
100%	100%	99%	98%	96%	94%	91%	88%	83%	77%	68%	56%	42%	29%	18%	10%	5%	2%	1%	0%	of 0°val

### Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
7379	7276	7088	6803	6291	5376	4007	2613	1602	1036	756	580	451	351	271	206	131	48	13	10	cd
100%	99%	96%	92%	85%	73%	54%	35%	22%	14%	10%	8%	6%	5%	4%	3%	2%	1%	0%	0%	of 0°val

### Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
7379	7368	7317	7231	7111	6953	6745	6488	6158	5700	5048	4158	3120	2128	1329	758	377	145	41	17	cd
100%	100%	99%	98%	96%	94%	91%	88%	83%	77%	68%	56%	42%	29%	18%	10%	5%	2%	1%	0%	of 0°val

### Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
7379	7276	7088	6803	6291	5376	4007	2613	1602	1036	756	580	451	351	271	206	131	48	13	10	cd
100%	99%	96%	92%	85%	73%	54%	35%	22%	14%	10%	8%	6%	5%	4%	3%	2%	1%	0%	0%	of 0°val

# Light Measurement Report

Print date: 2-9-2025

Measurement date and time: 2-9-2025 09:25:10 – Measurement no. VFR-250902-2869-MS

Measurement tracking No. and Link: [VT250902-002432](#)

Operator:



## Light Planning – UGR table

Uncorrected, comprehensive UGR table according to 117-1995

Reflectances		70	70	50	50	30	70	70	50	50	30
	ρ Ceiling	70	70	50	50	30	70	70	50	50	30
	ρ Walls	50	30	50	30	30	50	30	50	30	30
	ρ Floor	20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	28,3	29,3	28,5	29,6	29,8	20,4	21,4	20,6	21,7	21,9
	3H	29,1	30,1	29,5	30,4	30,6	20,9	21,9	21,3	22,2	22,4
	4H	29,4	30,4	29,8	30,6	30,9	21,2	22,2	21,6	22,5	22,7
	6H	29,6	30,4	29,9	30,7	31,1	21,6	22,4	21,9	22,7	23,1
	8H	29,6	30,4	29,9	30,7	31,2	21,7	22,5	22,0	22,8	23,2
	12H	29,6	30,4	29,9	30,7	31,2	21,7	22,5	22,1	22,8	23,3
4H	2H	28,0	29,0	28,4	29,3	29,5	20,9	21,8	21,3	22,1	22,4
	3H	29,0	29,8	29,4	30,2	30,6	21,6	22,4	22,0	22,8	23,2
	4H	29,3	30,0	29,7	30,5	31,0	21,9	22,7	22,4	23,1	23,7
	6H	29,5	30,2	30,0	30,6	31,0	22,3	23,0	22,8	23,4	23,8
	8H	29,6	30,2	30,1	30,6	31,0	22,4	23,1	23,0	23,5	23,9
	12H	29,6	30,1	30,1	30,5	31,0	22,5	23,0	23,0	23,5	24,0
8H	4H	29,2	29,9	29,7	30,2	30,6	22,2	22,8	22,7	23,2	23,6
	6H	29,5	29,9	30,0	30,4	31,0	22,6	23,1	23,2	23,6	24,1
	8H	29,6	30,0	30,1	30,5	31,2	22,9	23,3	23,4	23,8	24,4
	12H	29,6	30,0	30,2	30,5	31,1	23,0	23,3	23,6	23,8	24,4
12H	4H	29,2	29,7	29,7	30,1	30,6	22,2	22,7	22,7	23,1	23,6
	6H	29,5	29,9	30,0	30,4	31,1	22,7	23,1	23,2	23,6	24,3
	8H	29,5	29,9	30,1	30,4	31,0	22,9	23,2	23,5	23,8	24,4

### Variations with the observer position for the luminaire spacings, S:

S = 1.0H	0,5 / -0,7	1,0 / -0,9
S = 1.5H	1,8 / -2,1	1,9 / -1,2
S = 2.0H	3,1 / -3,5	2,7 / -1,8

## Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)																	
	Room Values are expressed as percentage of Lumen delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	106	106	106	101	101	101	99	
1	111	107	103	100	108	105	101	99	100	98	95	96	94	92	93	91	89	87
2	103	96	90	86	100	94	89	85	90	86	83	87	84	81	84	81	79	77
3	95	86	80	74	93	85	79	73	82	77	72	79	75	71	77	73	70	68
4	88	78	71	65	86	77	70	65	74	68	64	72	67	63	70	66	62	60
5	82	71	63	58	80	70	63	57	68	62	57	66	60	56	64	59	55	54
6	77	65	57	52	75	64	57	51	62	56	51	61	55	50	59	54	50	48
7	72	60	52	47	70	59	52	46	57	51	46	56	50	46	55	49	45	44
8	67	55	48	42	66	54	47	42	53	47	42	52	46	42	51	45	41	40
9	63	51	44	39	62	51	43	39	49	43	38	48	42	38	47	42	38	36
10	60	48	40	36	58	47	40	36	46	40	35	45	39	35	44	39	35	33

# Light Measurement Report

Print date: 2-9-2025

Measurement date and time: 2-9-2025 09:25:10 – Measurement no. VFR-250902-2869-MS

Measurement tracking No. and Link: [VT250902-002432](#)


Operator:



## Luminaire budgetary diagram

Uncorrected, comprehensive UGR table according to 117-1995

LAMPS (number of lamps)



### Conditions

H = Room height	Flux = 12922 lm				
H <sub>down</sub> = Lamp distance from ceiling =	0.00 m	Line type	Ceiling reflectance	ρ(%) Wall reflectance	Floor reflectance
H <sub>work</sub> = Work area height from floor =	0.00 m	-----	70	50	30
E <sub>work</sub> = Average lux on work area =	100 lx	—————	50	30	20

### Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
660 lm	1941 lm	2793 lm	2747 lm	2066 lm	1358 lm	761 lm	365 lm	103 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
16,2 lm	16,0 lm	17,4 lm	18,4 lm	18,2 lm	16,7 lm	13,3 lm	9,07 lm	3,13 lm

# Light Measurement Report

Print date: 2-9-2025

Measurement date and time: 2-9-2025 09:25:10 – Measurement no. VFR-250902-2869-MS

Measurement tracking No. and Link: [VT250902-002432](#)

Operator:



## Outdoor Light Planning

### Lumen per Zone

Zone (γ)	Lumen	% Total
0-10°	660 lm	5,1%
10-20°	1941 lm	15,0%
20-30°	2793 lm	21,6%
30-40°	2747 lm	21,3%
40-50°	2066 lm	16,0%
50-60°	1358 lm	10,5%
60-70°	761 lm	5,9%
70-80°	365 lm	2,8%
80-90°	103 lm	0,8%
90-100°	16 lm	0,1%
100-110°	16 lm	0,1%
110-120°	17 lm	0,1%
120-130°	18 lm	0,1%
130-140°	18 lm	0,1%
140-150°	17 lm	0,1%
150-160°	13 lm	0,1%
160-170°	9 lm	0,1%
170-180°	3 lm	0,0%
<b>Total</b>	<b>12922 lm</b>	<b>100,0%</b>

### Intensity peaks

Max intensity	7396 cd
Intensity, 90°	41 cd
Intensity, 0°	7379 cd

### Zonal Lumen summary


Zone (γ)	Lumen	% Total
0-30°	5394 lm	41,7%
0-40°	8141 lm	63,0%
0-60°	11565 lm	89,5%
60-90°	1229 lm	9,5%
70-100°	484 lm	3,7%
90-120°	50 lm	0,4%
0-90°	12794 lm	99,0%
90-180°	128 lm	1,0%
0-180°	12922 lm	100,0%

### BUG rating

	Lumen	% Total
<b>Forward light</b>		
Low(0-30°)	2739 lm	21,2%
Medium(30-60°)	3060 lm	23,7%
High(60-80°)	549 lm	4,3%
Very high(80-90°)	49 lm	0,4%
<b>Back light</b>		
Low(0-30°)	2739 lm	21,2%
Medium(30-60°)	3060 lm	23,7%
High(60-80°)	549 lm	4,3%
Very high(80-90°)	49 lm	0,4%
<b>Uplight</b>		
Low(90-100°)	17 lm	0,1%
High(100-180°)	112 lm	0,9%

## IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

**BUG rating B4 U3 G1**



# Light Measurement Report

Print date: 2-9-2025

Measurement date and time: 2-9-2025 09:25:10 – Measurement no. VFR-250902-2869-MS

Measurement tracking No. and Link: [VT250902-002432](#)

Operator:




## Power Details

### Input Power

Power feed to light source	77,2 W
Frequency of input power	50 Hz
RMS Input voltage feed, $V_{RMS}$	230 V
RMS Input current feed, $I_{RMS}$	0,343 A
Volt-Ampere or apparent power = $V_{RMS} * I_{RMS}$	78,89 VA
Displacement factor of AC power feed	0,98
Power factor of AC current feed	0,98
Total harmonic distortion of the current	7,72%
Total harmonic distortion of the voltage	0,14%

### Input Power Curve



### Efficiency

Radiated power efficiency 51,0%



Lumen efficiency 167 lm/W



## Stabilization Details

### Warmup Conditions

Stable period	15 min
Stable change max	2,0%
Minimum time	15 min

### Color Temperature Change

CCT start	5695 K
CCT shift	+5 K
CCT end	5700 K


### Warmup Result

Total warmup time	Lamp stabilized in 15 min 1 sec
Warmup variation	-1,2%

### Output Change

Output start	13078 lm
Output change	-156 lm
Output end	12922 lm

### Stabilization Curve



# Light Measurement Report

Print date: 2-9-2025

Measurement date and time: 2-9-2025 09:25:10 – Measurement no. VFR-250902-2869-MS

Measurement tracking No. and Link: [VT250902-002432](#)

Operator:



## Flicker /TLA details

Flicker Meter Type Viso Systems LabFlicker  
 Frequency of input power 50 Hz  
 Flicker/TLA sample rate 20000 samples/s

**Measurement time**  
 PstLM 180 sec  
 All other indices 1,2 sec

### Flicker indices according to Illuminating Engineering Society (IES)

Flicker frequency 100 Hz  
 Percent Flicker 0,27 %  
 Flicker index 0

### Flicker indices according to California Energy Commission (CEC) 2016b

JA8/10 40 Hz 0,02 %  
 JA8/10 90 Hz 0,02 %  
 JA8/10 200 Hz 0,26 %  
 JA8/10 400 Hz 0,25 %  
 JA8/10 1000 Hz 0,26 %


### TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)

PstLM value (F < 80 Hz) 0,01  
 SVM value (80 < F < 2000 Hz) 0,01

### Flicker indices according to Lighting Research Center (2015)

Perception metric, Assist Mp 0,01

### Flicker frame (frame of one flicker period in time domain)



### Flicker FFT (flicker curve in frequency domain)



### IEEE 1789 Frequency/modulation plot

