

Light Measurement Report

Print date: 6-5-2025

Measurement date and time: 6-5-2025 13:53:13 – Measurement no. VFR-250506-1105-MS

Measurement tracking No. and Link: [VT250506-005997](#)

Operator:



Laboratory and Equipment

Laboratory Owner and Location

Goniospectrometer System and Type

Sensor Name, Calibr. Date and Serial No.

Spectrometer Manufacturer and Model

Viso Systems, Copenhagen V, Denmark

LabSpion – Type C, horizontal

LabSensor Model2 – 11-1-2024 – 3130191315

Ibsen Photonics, Denmark – Freedom VIS (Custom Viso)

Measurement Conditions

Number of C-planes and Resolution

γ (gamma)-Resolution

Test Distance

Input Power, Power and Displ. Factors

Input RMS Voltage and Current

Frequency of Input Power

Warm-up Time and Variation

16 planes – 22,5°

5°

2,00 m

6,6 W – PF 0,51 – DPF 0,87

230 V – 0,055 A

50 Hz

Lamp stabilized in 22 min 2 sec – 2,0%

Tested Light Source

Product Name

Item No. and Manufacturer

Product Description (line 1)

845635-4000K

845635-4000K – Dutchfulfillment

3-FASE RAILSPOT ELARA 7W WIT

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)

Efficiency

Peak Intensity and Beam Angle

Correlated Color Temperature, Target/Measured

Color Rendering Index

Color Rendering TM30-18

Color Shift, CIE duv and MacAdam Steps

Flicker

602 lm – 0,04% / 99,96%

92 lm/W

1223 cd – 40,4°



CCT = 4000 K / 4071 K

CRI 83,3

R_f 84,3 – R_g 95,1

Duv 0,0006 – SDCM 1,6

SVM 0,02 – PstLM 0,05



Light Measurement Report

Print date: 6-5-2025

Measurement date and time: 6-5-2025 13:53:13 – Measurement no. VFR-250506-1105-MS


Measurement tracking No. and Link: [VT250506-005997](#)

Operator:



Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	602 lm
Lumen Up% / Down%	0,04% / 99,96%
Peak Intensity	1223 cd
Beam Angle (50%)	40,4°
Beam Angle (90%)	39,3°
Beam Angle (10%)	41,7°

Cut-off Angle

Average 2,5%	82,1°
--------------	-------

Field Angle

Average 10%	69,4°
-------------	-------


Intensity Ratio

In 120° cone	99,9%
In 90° cone	99,4%

C000-C180

C090-C270

Linear distribution diagram - Intensity (candela) vs γ-angle




Light Measurement Report


Print date: 6-5-2025
Measurement date and time: 6-5-2025 13:53:13 – Measurement no. VFR-250506-1105-MS
Measurement tracking No. and Link: [VT250506-005997](#)
Operator:



Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)



Light Measurement Report

Print date: 6-5-2025

Measurement date and time: 6-5-2025 13:53:13 – Measurement no. VFR-250506-1105-MS

Measurement tracking No. and Link: [VT250506-005997](https://vfr-250506-1105-MS)

Operator:




Color details


Correlated Color Temperature, Target CCT = 4000 K
Correlated Color Temperature, Measured CCT = 4071 K
Color Rendering Index CRI 83,3
Color Rendering Index, R9 (red component) R9 = 6,9
Color Rendering TM30-18 R_f 84,3 – R_g 95,1
Color Quality Scale CQS = 82,4

MacAdam Steps
Color coordinates CIE 1931 (x;y) = (0,381;0,377)
Color coordinate CIEs 1960 (u;v) = (0,225;0,334)
Color deviation from BBL Duv = 0,0006
Color coordinate CIEs 1976 (CIELUV) (u';v') = (0,225;0,502)


CIE 1931



CIE 1931 – zoomed on Planckian locus




Color Rendering Index per reference color (CIE 1995)




CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
81,6	89,7	95,5	82,4	81,7	85,8	85,8	64,1	6,9	75,7	81,8	62,7	83,8	97,8	74,3

Spectral power distribution (SPD) / W/nm – 0-100%




TM30-18 R_f-values per hue bin



TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
79,8	83,2	78,4	88,3	90,6	94,7	91,8	89,8	86,9	78,1	78,5	83,5	86,2	86,4	77,4	77,5

Color Quality Scale by reference color



CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
80,9	98,2	79,8	76,5	81,4	83,5	85,4	88,8	97,7	89,1	85,6	83,8	83,0	71,1	74,7

Light Measurement Report

Print date: 6-5-2025


Measurement date and time: 6-5-2025 13:53:13 – Measurement no. VFR-250506-1105-MS

Measurement tracking No. and Link: [VT250506-005997](#)

Operator:



Beam Details



Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3,3	6,6	9,8	13,1	16,4	19,7	23	26,2	29,5	32,8	36,1	39,4	42,7	45,9	49,2	52,5	55,8	59,1	62,3	65,6	ft
1205	301	134	75	48	33	25	19	15	12	10	8	7	6	5	5	4	4	3	3	lux
111,9	28	12,4	7	4,5	3,1	2,3	1,7	1,4	1,1	0,9	0,8	0,7	0,6	0,5	0,4	0,4	0,3	0,3	0,3	fc

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
1205	1172	1172	1164	1101	1039	963	879	795	709	623	538	454	373	309	245	193	146	102	72	cd
100%	97%	97%	97%	91%	86%	80%	73%	66%	59%	52%	45%	38%	31%	26%	20%	16%	12%	8%	6%	of 0°val

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
1205	1211	1182	1153	1095	1025	951	862	772	682	592	505	427	350	282	219	160	116	72	47	cd
100%	100%	98%	96%	91%	85%	79%	72%	64%	57%	49%	42%	35%	29%	23%	18%	13%	10%	6%	4%	of 0°val

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
1205	1172	1172	1164	1101	1039	963	879	795	709	623	538	454	373	309	245	193	146	102	72	cd
100%	97%	97%	97%	91%	86%	80%	73%	66%	59%	52%	45%	38%	31%	26%	20%	16%	12%	8%	6%	of 0°val

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
1205	1211	1182	1153	1095	1025	951	862	772	682	592	505	427	350	282	219	160	116	72	47	cd
100%	100%	98%	96%	91%	85%	79%	72%	64%	57%	49%	42%	35%	29%	23%	18%	13%	10%	6%	4%	of 0°val

Light Measurement Report

Print date: 6-5-2025

Measurement date and time: 6-5-2025 13:53:13 – Measurement no. VFR-250506-1105-MS

Measurement tracking No. and Link: [VT250506-005997](#)

Operator:



Light Planning – UGR table

Uncorrected, comprehensive UGR table according to 117-1995

Reflectances											
	ρ Ceiling	70	70	50	50	30	70	70	50	50	30
	ρ Walls	50	30	50	30	30	50	30	50	30	30
	ρ Floor	20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	16,7	17,3	16,8	17,5	17,7	15,4	15,9	15,4	16,1	16,3
	3H	16,4	17,1	16,8	17,3	17,5	15,0	15,7	15,4	15,9	16,1
	4H	16,3	17,0	16,7	17,2	17,4	15,0	15,6	15,4	15,9	16,1
	6H	16,3	16,9	16,6	17,2	17,5	15,0	15,5	15,3	15,8	16,2
	8H	16,3	16,8	16,6	17,1	17,5	14,9	15,4	15,2	15,8	16,1
	12H	16,2	16,7	16,6	17,1	17,5	14,9	15,4	15,2	15,7	16,1
4H	2H	16,3	17,0	16,7	17,2	17,4	15,0	15,6	15,4	15,9	16,1
	3H	16,2	16,7	16,6	17,1	17,5	14,9	15,4	15,2	15,7	16,1
	4H	16,1	16,5	16,5	17,0	17,5	14,7	15,2	15,1	15,6	16,1
	6H	16,0	16,5	16,5	16,8	17,2	14,6	15,1	15,1	15,5	15,8
	8H	15,9	16,4	16,5	16,7	17,1	14,6	15,0	15,1	15,4	15,7
	12H	15,9	16,2	16,4	16,6	17,1	14,5	14,9	15,0	15,3	15,7
8H	4H	15,9	16,4	16,5	16,7	17,1	14,6	15,0	15,1	15,4	15,7
	6H	15,9	16,2	16,4	16,6	17,2	14,5	14,8	15,0	15,3	15,8
	8H	15,9	16,1	16,4	16,6	17,2	14,5	14,7	15,0	15,3	15,9
	12H	15,8	16,0	16,4	16,5	17,1	14,4	14,6	15,0	15,1	15,7
12H	4H	15,9	16,2	16,4	16,6	17,1	14,5	14,9	15,0	15,3	15,7
	6H	15,9	16,1	16,4	16,6	17,2	14,5	14,7	15,0	15,3	15,9
	8H	15,8	16,0	16,4	16,5	17,1	14,4	14,6	15,0	15,1	15,7
Variations with the observer position for the luminaire spacings, S:											
S = 1.0H		5,8 / -21,3					6,0 / -21,5				
S = 1.5H		8,6 / -25,0					8,7 / -24,1				
S = 2.0H		10,5 / -27,1					10,7 / -26,3				

Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR		(RCR: Room Cavity Ratio)			Room Values are expressed as percentage of Lumen delivered to the task surface													
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95
2	110	105	102	99	107	104	100	98	100	98	96	98	95	94	95	93	92	90
3	105	100	95	92	103	98	94	91	96	92	90	93	91	88	91	89	87	85
4	101	94	90	86	99	93	89	85	91	87	84	89	86	83	87	85	82	81
5	97	89	84	81	95	89	84	80	87	83	80	85	82	79	84	81	78	77
6	93	85	80	76	91	84	80	76	83	79	76	82	78	75	80	77	75	73
7	89	81	76	72	88	81	76	72	79	75	72	78	74	71	77	74	71	70
8	86	77	72	69	85	77	72	69	76	72	68	75	71	68	74	71	68	67
9	82	74	69	66	81	74	69	65	73	68	65	72	68	65	71	68	65	64
10	79	71	66	63	78	71	66	63	70	65	62	69	65	62	68	65	62	61

Light Measurement Report


Print date: 6-5-2025
Measurement date and time: 6-5-2025 13:53:13 – Measurement no. VFR-250506-1105-MS
Measurement tracking No. and Link: [VT250506-005997](#)
Operator:



Luminaire budgetary diagram

Uncorrected, comprehensive UGR table according to 117-1995

LAMPS (number of lamps)



Conditions

H = Room height	Flux = 602 lm	p(%)		
H _{down} = Lamp distance from ceiling =	0.00 m	Line type	Ceiling reflectance	Wall reflectance
H _{work} = Work area height from floor =	0.00 m		70	50
E _{work} = Average lux on work area =	100 lx		50	30
				Floor reflectance
				30
				20

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
108 lm	229 lm	183 lm	71,0 lm	8,44 lm	1,01 lm	0,331 lm	0,103 lm	0,028 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0,013 lm	0,002 lm	0,001 lm	0,002 lm	0,010 lm	0,044 lm	0,084 lm	0,069 lm	0,021 lm

Light Measurement Report

Print date: 6-5-2025

Measurement date and time: 6-5-2025 13:53:13 – Measurement no. VFR-250506-1105-MS

Measurement tracking No. and Link: [VT250506-005997](#)

Operator:



Outdoor Light Planning

Lumen per Zone

Zone (γ)	Lumen	% Total
0-10°	108 lm	18,0%
10-20°	229 lm	38,1%
20-30°	183 lm	30,5%
30-40°	71 lm	11,8%
40-50°	8 lm	1,4%
50-60°	1 lm	0,2%
60-70°	0 lm	0,1%
70-80°	0 lm	0,0%
80-90°	0 lm	0,0%
90-100°	0 lm	0,0%
100-110°	0 lm	0,0%
110-120°	0 lm	0,0%
120-130°	0 lm	0,0%
130-140°	0 lm	0,0%
140-150°	0 lm	0,0%
150-160°	0 lm	0,0%
160-170°	0 lm	0,0%
170-180°	0 lm	0,0%
Total	602 lm	100,0%

Intensity peaks

Max intensity	1223 cd
Intensity, 90°	0 cd
Intensity, 0°	1205 cd

Zonal Lumen summary

Zone (γ)	Lumen	% Total
0-30°	521 lm	86,5%
0-40°	592 lm	98,3%
0-60°	601 lm	99,9%
60-90°	0 lm	0,1%
70-100°	0 lm	0,0%
90-120°	0 lm	0,0%
0-90°	602 lm	100,0%
90-180°	0 lm	0,0%
0-180°	602 lm	100,0%

BUG rating

	Lumen	% Total
Forward light		
Low(0-30°)	258 lm	42,9%
Medium(30-60°)	42 lm	7,0%
High(60-80°)	0 lm	0,0%
Very high(80-90°)	0 lm	0,0%
Back light		
Low(0-30°)	258 lm	42,9%
Medium(30-60°)	42 lm	7,0%
High(60-80°)	0 lm	0,0%
Very high(80-90°)	0 lm	0,0%


Uplight

Low(90-100°)	0 lm	0,0%
High(100-180°)	0 lm	0,0%

IESNA TM-15-07

Luminaire Classification System For Outdoor Luminaires

BUG rating B1 U0 G0



Light Measurement Report

Print date: 6-5-2025
Measurement date and time: 6-5-2025 13:53:13 – Measurement no. VFR-250506-1105-MS
Measurement tracking No. and Link: [VT250506-005997](#)
Operator:




Power Details


Input Power

Power feed to light source	6,6 W
Frequency of input power	50 Hz
RMS Input voltage feed, V_{RMS}	230 V
RMS Input current feed, I_{RMS}	0,055 A
Volt-Ampere or apparent power = $V_{RMS} * I_{RMS}$	12,76 VA
Displacement factor of AC power feed	0,87
Power factor of AC current feed	0,51
Total harmonic distortion of the current	131,78%
Total harmonic distortion of the voltage	0,07%

Input Power Curve



Efficiency



Stabilization Details

Warmup Conditions

Stable period	15 min
Stable change max	2,0%
Minimum time	15 min

Color Temperature Change

CCT start	3971 K
CCT shift	+29 K
CCT end	4000 K


Warmup Result

Total warmup time	Lamp stabilized in 22 min 2 sec
Warmup variation	-3,8%

Output Change

Output start	625 lm
Output change	-24 lm
Output end	602 lm

Stabilization Curve



Light Measurement Report


Print date: 6-5-2025
Measurement date and time: 6-5-2025 13:53:13 – Measurement no. VFR-250506-1105-MS
Measurement tracking No. and Link: [VT250506-005997](#)
Operator:




Flicker /TLA details

Flicker Meter Type	Viso Systems LabFlicker	Measurement time	
Frequency of input power	50 Hz	PstLM	180 sec
Flicker/TLA sample rate	20000 samples/s	All other indices	1,2 sec
Flicker indices according to Illuminating Engineering Society (IES)		Flicker indices according to California Energy Commission (CEC) 2016b	
Flicker frequency	100 Hz	JA8/10 40 Hz	0,03 %
Percent Flicker	0,55 %	JA8/10 90 Hz	0,03 %
Flicker index	0	JA8/10 200 Hz	0,47 %
TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)		JA8/10 400 Hz	0,55 %
PstLM value (F < 80 Hz)	0,05	JA8/10 1000 Hz	0,55 %
SVM value (80 < F < 2000 Hz)	0,02	Flicker indices according to Lighting Research Center (2015)	
		Perception metric, Assist Mp	0,01

Flicker frame (frame of one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789 Frequency/modulation plot

