

Light Measurement Report

Print date: 31-10-2024
Measurement date and time: 31-10-2024 09:54:19 – Measurement no. VFR-241031-1750-MS
Measurement tracking No. and Link: [VT241031-004149](#)
Operator:



Laboratory and Equipment

Laboratory Owner and Location	Viso Systems, Copenhagen V, Denmark
Goniospectrometer System and Type	LabSpion – Type C, horizontal
Sensor Name, Calibr. Date and Serial No.	LabSensor Model2 – 11-1-2024 – 3130191315
Spectrometer Manufacturer and Model	Ibsen Photonics, Denmark – Freedom VIS (Custom Viso)

Measurement Conditions



Number of C-planes and Resolution	28 planes – 12,86°
γ (gamma)-Resolution	5°
Test Distance	1,99 m
Input Power, Power and Displ. Factors	1,5 W – PF 0,32 – DPF 1,0
Input RMS Voltage and Current	230 V – 0,020 A
Frequency of Input Power	50 Hz
Warm-up Time and Variation	Not completed – 2,0%

Tested Light Source

Product Name	FUT061-BLAUW
Item No. and Manufacturer	FUT061-BLAUW – Dutchfulfillment
Product Description (line 1)	MI-LIGHT DOWNLIGHT RGB+CCT Ø110 9W WIT

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)	9,10 lm – 2,65% / 97,35%
Efficiency	6 lm/W
Peak Intensity and Beam Angle	3,22 cd – 110°
Correlated Color Temperature, Target/Measured	CCT = 0 K / 0 K
Color Rendering Index	CRI 0,0
Color Rendering TM30-18	R _f 0,0 – R _g 0,0
Color Shift, CIE duv and MacAdam Steps	Duv n/a – SDCM n/a
Flicker	SVM 0 – PstLM 0,04



Light Measurement Report

Print date: 31-10-2024

Measurement date and time: 31-10-2024 09:54:19 – Measurement no. VFR-241031-1750-MS


Measurement tracking No. and Link: [VT241031-004149](#)

Operator:



Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	9,10 lm
Lumen Up% / Down%	2,65% / 97,35%
Peak Intensity	3,22 cd
Beam Angle (50%)	110°
Beam Angle (90%)	110°
Beam Angle (10%)	110°

Cut-off Angle

Average 2,5%	173,5°
--------------	--------

Field Angle

Average 10%	158,6°
-------------	--------


Intensity Ratio

In 120° cone	77,8%
In 90° cone	53,4%

C000-C180

C090-C270

Linear distribution diagram - Intensity (candela) vs γ-angle




Light Measurement Report


Print date: 31-10-2024
Measurement date and time: 31-10-2024 09:54:19 – Measurement no. VFR-241031-1750-MS
Measurement tracking No. and Link: [VT241031-004149](#)
Operator:



Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)



Light Measurement Report

Print date: 31-10-2024
Measurement date and time: 31-10-2024 09:54:19 – Measurement no. VFR-241031-1750-MS
Measurement tracking No. and Link: [VT241031-004149](#)
Operator:



Color details

Correlated Color Temperature, Target

Correlated Color Temperature, Measured

Color Rendering Index

Color Rendering Index, R9 (red component)

Color Rendering TM30-18

Color Quality Scale

CCT = 0 K

CCT = 0 K

CRI 0,0

R9 = 0,0

R_f 0,0 – R_g 0,0

CQS = 0,0

MacAdam Steps

Color coordinates CIE 1931

Color coordinate CIEs 1960

Color deviation from BBL

Color coordinate CIEs 1976 (CIELUV)



SDCM = n/a

(x;y) = (0,148;0,050)

(u;v) = (0,179;0,090)

Duv = n/a

(u';v') = (0,179;0,135)



Color Rendering Index per reference color (CIE 1995)

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15	

CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0


TM30-18 Rf-values per hue bin

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0

Spectral power distribution (SPD) / W/nm – 0-100%



Color Quality Scale by reference color

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15	

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0	0,0

Light Measurement Report

Print date: 31-10-2024


Measurement date and time: 31-10-2024 09:54:19 – Measurement no. VFR-241031-1750-MS

Measurement tracking No. and Link: [VT241031-004149](#)

Operator:



Beam Details



Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3,3	6,6	9,8	13,1	16,4	19,7	23	26,2	29,5	32,8	36,1	39,4	42,7	45,9	49,2	52,5	55,8	59,1	62,3	65,6	ft
3	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	lux
0,3	0,1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	fc

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
3,22	3,22	3,17	3,10	2,99	2,86	2,68	2,49	2,29	2,06	1,86	1,61	1,34	1,08	0,80	0,55	0,29	0,10	0,05	0,04	cd
100%	100%	99%	96%	93%	89%	83%	78%	71%	64%	58%	50%	42%	33%	25%	17%	9%	3%	2%	1%	of 0°val

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
3,22	3,22	3,17	3,10	2,99	2,86	2,68	2,49	2,29	2,06	1,86	1,61	1,34	1,08	0,80	0,55	0,29	0,10	0,05	0,04	cd
100%	100%	99%	96%	93%	89%	83%	78%	71%	64%	58%	50%	42%	33%	25%	17%	9%	3%	2%	1%	of 0°val

Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
3,22	3,22	3,17	3,10	2,99	2,86	2,68	2,49	2,29	2,06	1,86	1,61	1,34	1,08	0,80	0,55	0,29	0,10	0,05	0,04	cd
100%	100%	99%	96%	93%	89%	83%	78%	71%	64%	58%	50%	42%	33%	25%	17%	9%	3%	2%	1%	of 0°val

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°	γ
3,22	3,22	3,17	3,10	2,99	2,86	2,68	2,49	2,29	2,06	1,86	1,61	1,34	1,08	0,80	0,55	0,29	0,10	0,05	0,04	cd
100%	100%	99%	96%	93%	89%	83%	78%	71%	64%	58%	50%	42%	33%	25%	17%	9%	3%	2%	1%	of 0°val

Light Measurement Report

Print date: 31-10-2024

Measurement date and time: 31-10-2024 09:54:19 – Measurement no. VFR-241031-1750-MS

Measurement tracking No. and Link: [VT241031-004149](#)

Operator:



Light Planning – UGR table

Uncorrected, comprehensive UGR table according to 117-1995

Reflectances											
	ρ Ceiling	70	70	50	50	30	70	70	50	50	30
	ρ Walls	50	30	50	30	30	50	30	50	30	30
	ρ Floor	20	20	20	20	20	20	20	20	20	20
Room size											
H = mounting height above eye level											
X	Y	Viewed Crosswise (Viewing direction orthogonal to lamp length axis)					Viewed Endwise (Viewing direction parallel to lamp length axis)				
2H	2H	8,7	9,8	8,9	10,2	10,5	8,7	9,8	8,9	10,2	10,5
	3H	9,9	11,1	10,3	11,4	11,7	9,9	11,1	10,3	11,4	11,7
	4H	10,4	11,5	10,8	11,8	12,2	10,4	11,5	10,8	11,8	12,2
	6H	10,7	11,7	11,0	12,0	12,5	10,7	11,7	11,0	12,0	12,5
	8H	10,7	11,7	11,1	12,1	12,5	10,7	11,7	11,1	12,1	12,5
	12H	10,7	11,7	11,1	12,0	12,5	10,7	11,7	11,1	12,0	12,5
4H	2H	9,2	10,3	9,6	10,7	11,0	9,2	10,3	9,6	10,7	11,0
	3H	10,7	11,7	11,1	12,1	12,5	10,7	11,7	11,1	12,1	12,5
	4H	11,2	12,1	11,7	12,6	13,1	11,2	12,1	11,7	12,6	13,1
	6H	11,6	12,4	12,1	12,8	13,2	11,6	12,4	12,1	12,8	13,2
	8H	11,6	12,4	12,2	12,8	13,2	11,6	12,4	12,2	12,8	13,2
	12H	11,6	12,3	12,2	12,7	13,3	11,6	12,3	12,2	12,7	13,3
8H	4H	11,4	12,2	12,0	12,6	13,0	11,4	12,2	12,0	12,6	13,0
	6H	11,9	12,4	12,4	12,9	13,5	11,9	12,4	12,4	12,9	13,5
	8H	12,0	12,5	12,5	13,1	13,7	12,0	12,5	12,5	13,1	13,7
	12H	12,0	12,5	12,7	13,0	13,7	12,0	12,5	12,7	13,0	13,7
12H	4H	11,4	12,0	11,9	12,5	13,0	11,4	12,0	11,9	12,5	13,0
	6H	11,9	12,4	12,4	13,0	13,6	11,9	12,4	12,4	13,0	13,6
	8H	12,0	12,4	12,6	13,0	13,6	12,0	12,4	12,6	13,0	13,6
Variations with the observer position for the luminaire spacings, S:											
S = 1.0H		0,1 / -0,1					0,1 / -0,1				
S = 1.5H		0,2 / -0,4					0,2 / -0,4				
S = 2.0H		0,6 / -0,8					0,6 / -0,8				

Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR		(RCR: Room Cavity Ratio)			Room Values are expressed as percentage of Lumen delivered to the task surface													
0	118	118	118	118	115	115	115	115	115	110	110	104	104	104	100	100	100	97
1	108	104	99	96	105	101	97	94	96	93	90	92	90	87	88	86	84	82
2	99	90	84	78	96	88	82	77	84	79	75	81	76	73	77	74	71	68
3	90	80	71	65	87	78	70	64	74	68	63	71	66	61	68	64	60	58
4	82	70	62	55	80	69	61	55	66	59	54	63	57	53	61	56	52	49
5	76	63	54	47	73	62	53	47	59	52	46	57	51	46	55	49	45	43
6	70	57	48	41	68	56	47	41	54	46	41	52	45	40	50	44	39	37
7	65	51	43	37	63	50	42	36	49	41	36	47	40	35	45	40	35	33
8	60	47	38	33	59	46	38	32	45	37	32	43	37	32	42	36	31	29
9	56	43	35	29	55	42	35	29	41	34	29	40	33	29	39	33	28	27
10	53	40	32	27	51	39	32	27	38	31	26	37	31	26	36	30	26	24

Light Measurement Report


Print date: 31-10-2024
Measurement date and time: 31-10-2024 09:54:19 – Measurement no. VFR-241031-1750-MS
Measurement tracking No. and Link: [VT241031-004149](#)
Operator:



Luminaire budgetary diagram

Uncorrected, comprehensive UGR table according to 117-1995

LAMPS (number of lamps)



Conditions

H = Room height	Flux = 9,10 lm	p(%)		
H _{down} = Lamp distance from ceiling =	0.00 m	Line type	Ceiling reflectance	Wall reflectance
H _{work} = Work area height from floor =	0.00 m	-----	70	50
E _{work} = Average lux on work area =	100 lx	_____	50	30
				Floor reflectance
				20

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
0,305 lm	0,872 lm	1,31 lm	1,56 lm	1,60 lm	1,43 lm	1,06 lm	0,574 lm	0,143 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0,045 lm	0,040 lm	0,035 lm	0,035 lm	0,030 lm	0,021 lm	0,019 lm	0,012 lm	0,004 lm

Light Measurement Report

Print date: 31-10-2024
Measurement date and time: 31-10-2024 09:54:19 – Measurement no. VFR-241031-1750-MS
Measurement tracking No. and Link: [VT241031-004149](#)
Operator:



Outdoor Light Planning

Lumen per Zone

Zone (γ)	Lumen	% Total
0-10°	0 lm	3,4%
10-20°	1 lm	9,6%
20-30°	1 lm	14,4%
30-40°	2 lm	17,1%
40-50°	2 lm	17,6%
50-60°	1 lm	15,8%
60-70°	1 lm	11,6%
70-80°	1 lm	6,3%
80-90°	0 lm	1,6%
90-100°	0 lm	0,5%
100-110°	0 lm	0,4%
110-120°	0 lm	0,4%
120-130°	0 lm	0,4%
130-140°	0 lm	0,3%
140-150°	0 lm	0,2%
150-160°	0 lm	0,2%
160-170°	0 lm	0,1%
170-180°	0 lm	0,0%
Total	9 lm	100,0%

Intensity peaks

Max intensity	3 cd
Intensity, 90°	0 cd
Intensity, 0°	3 cd

Zonal Lumen summary


Zone (γ)	Lumen	% Total
0-30°	2 lm	27,4%
0-40°	4 lm	44,5%
0-60°	7 lm	77,8%
60-90°	2 lm	19,5%
70-100°	1 lm	8,4%
90-120°	0 lm	1,3%
0-90°	9 lm	97,3%
90-180°	0 lm	2,7%
0-180°	9 lm	100,0%

BUG rating

	Lumen	% Total
Forward light		
Low(0-30°)	1 lm	13,7%
Medium(30-60°)	2 lm	25,2%
High(60-80°)	1 lm	9,0%
Very high(80-90°)	0 lm	0,8%
Back light		
Low(0-30°)	1 lm	13,7%
Medium(30-60°)	2 lm	25,2%
High(60-80°)	1 lm	9,0%
Very high(80-90°)	0 lm	0,8%
Uplight		
Low(90-100°)	0 lm	0,5%
High(100-180°)	0 lm	2,2%

IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B0 U0 G0



Light Measurement Report

Print date: 31-10-2024
Measurement date and time: 31-10-2024 09:54:19 – Measurement no. VFR-241031-1750-MS
Measurement tracking No. and Link: [VT241031-004149](#)
Operator:




Power Details

Input Power

Power feed to light source	1,5 W
Frequency of input power	50 Hz
RMS Input voltage feed, V_{RMS}	230 V
RMS Input current feed, I_{RMS}	0,020 A
Volt-Ampere or apparent power = $V_{RMS} * I_{RMS}$	4,55 VA
Displacement factor of AC power feed	1,0
Power factor of AC current feed	0,32
Total harmonic distortion of the current	291,24%
Total harmonic distortion of the voltage	0,07%

Input Power Curve



Efficiency

Radiated power efficiency	10,1%
Lumen efficiency	6 lm/W

Stabilization Details

Warmup Conditions

Stable period	15 min
Stable change max	2,0%
Minimum time	15 min

Color Temperature Change

CCT start	0 K
CCT shift	0 K
CCT end	0 K


Warmup Result

Total warmup time	Not completed
Warmup variation	-0,9%

Output Change

Output start	9,10 lm
Output change	0,00 lm
Output end	9,10 lm

Stabilization Curve



Light Measurement Report


Print date: 31-10-2024
Measurement date and time: 31-10-2024 09:54:19 – Measurement no. VFR-241031-1750-MS
Measurement tracking No. and Link: [VT241031-004149](#)
Operator:



Flicker /TLA details

Flicker Meter Type	Viso Systems LabFlicker	Measurement time	
Frequency of input power	50 Hz	PstLM	180 sec
Flicker/TLA sample rate	20000 samples/s	All other indices	1,2 sec
Flicker indices according to Illuminating Engineering Society (IES)		Flicker indices according to California Energy Commission (CEC) 2016b	
Flicker frequency	10000 Hz	JA8/10 40 Hz	0,05 %
Percent Flicker	0,3 %	JA8/10 90 Hz	0,06 %
Flicker index	0	JA8/10 200 Hz	0,12 %
		JA8/10 400 Hz	0,13 %
		JA8/10 1000 Hz	0,14 %
TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)		Flicker indices according to Lighting Research Center (2015)	
PstLM value (F < 80 Hz)	0,04	Perception metric, Assist Mp	0,02
SVM value (80 < F < 2000 Hz)	0		

Flicker frame (frame of one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789 Frequency/modulation plot

